

Base de Conhecimentos > Products > Industrial HiVision > Security Status Screen and Security Lock Down

Security Status Screen and Security Lock Down

- 2018-02-21 - Industrial HiVision

Security Status Screen and Security Lock Down

This lesson explains the Security Status Screen and the Security Lockdown feature. Both is available in Industrial HiVision as of v06.0.

Security Status Screen



The new tab Security Status offers a device overview from a security point of view. All enabled unsecure protocols detected will be marked with an exclamation mark. If the protocol is supported but disabled then a padlock is displayed - status secure. Protocols not supported by the device is shown with a '-' and if protocols are not monitored a blank page is shown.

Configure Monitoring

Map	Map Lat Devices Parts Connectors Properties Security Status															
Beload							Device Classe All •					Osplay @ Configure Monitoring Activate all Deactivate all				
Typ	e :	Status	Nane	Tfp	Profinet 10	Http	EC61850	802-1X P A	Ethernet/IP	SIMP V1/V2	MIT Rule St	Teinet	Unused Act	Default Pas		
		4	02.14L17.140	1	(P)	1	12	(W)	×.	1	(V)	(X)	1	× .		
1 53		<u>a</u>	82,141,17,145	1	4	4	4	4	4	1	4	1	4	1		
	1	<u>a</u> .	82,141,17,134	1	1	1	1	1	1	1	1	1	1	1		
1 10		<u>.</u>	02.14L17.149	1	1	1	1	1	1	1	1	1	1	1		
-		à.	82,141,17,143	V	4	4	1	1	1	×.	V	1	4	V		
				100	1000	1.1	1.00		100	100	1000	100	100			

You can configure which protocols should be monitored.

The radio button allows you to switch between Display and Configuration.

If Configure Monitoring is selected you can selectively enable or disable monitoring of a

certain protocol per device or use the Activate/Deactivate all buttons.

Security Lock Down

Мар	List D	evices Ports C	onnectors Prop	erties Securit	y Status									
Beloa	d					Device Class: All +						Display	Configure Ma	nitoring Act
Type	Status	Name	Tfp	Profnet ID	Http	IEC61850	802.10	(P,A)	Ethernet/IP	SNMP V1/V2	ANY Rule St	Teinet	Unused Acti	Default Pas
	Â	82.141.17.140 82.141.17.145	4	9193	Â	9		1	레레	4	919	<u>^</u>	Â	<u>^</u>
-	<u> </u>	82,141,17,134		4	<u> </u>					\$	6	<u> </u>	<u> </u>	<u> </u>
10	<u> </u>	82.141.17.149	<u>&</u>	- 9	<u> </u>	1 /9	-	2	<u>ģ</u>	<u> </u>		<u> </u>	<u> </u>	<u> </u>
1 1 1 1 1 2 1 1 C 1 2	A A A A A A A A A A A A A A A A A A A	32,141,17,141 82,141,17,141 82,141,17,139 92,141,17,139 92,141,17,131 92,141,17,139 82,141,17,139 82,141,17,139 92,141,17,139 82,141,17,136 82,141,17,139 82,141,17,139	د دار دار دار دار دار دار دار دار دار دا	ත හි	4 4 4 4 4 4 4 4 4 4 4 4	म वी यो वी वी वी वी वी वी वी वी व	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	New Gut Copy Delete Betrest Manag Unmar Set De	h 94 vice and Port 1	Ctri- Ctri- Dele IS	-X -C	त्या से से से या से से या से या .	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	**************************************
	A À À	02.141.17.135 82.141.17.153 02.141.17.130	0000	ලිංහුව	थ वा ४	1141141	2 (6	Docum SNMP Ackno Guana MultiC	nent Selected Browser wiedge Status Config [™]	Devices Change Ctri-	-R	<mark>4</mark> यो <mark>अ</mark>	A A A	*

The Security Lockdown is available in MultiConfig.

- 1. Highlight the relevant devices
- 2. Select MultiConfig from the context menu or press $\mbox{Ctrl+M}$

Security Lock Down 2



With the Security Lock down dialog you can disable unsecure protocols on multiple devices at the push of a button.evices at the push of a button.